

- Built-in microSD slot
- Built-in microphone
- Metal casing
- Support for PoE
- IR illumination up to 40 m
- Configuration via web interface
- ONVIF



The **SV-BA314-E rev.B** wired IP camera with a dome design provides a horizontal viewing angle of 112° and is equipped with a 4 MP CMOS matrix for clear video with a resolution of up to 2560 × 1440. The device has a night shooting mode (IR illumination), motion detection system and the function of saving the video archive to a memory card or network storage¹. The camera is equipped with an RJ-45 connector with support for basic network protocols.

Technical features

Interfaces

Ethernet 1 × 10/100BASE-T (RJ-45), support for PoE

Memory card 1 × MicroSD/SDHC/SDXC up to 512 GB

Network

Protocols TCP/IP, UDP, ICMP, HTTP, HTTPS, SSL/TLS, QoS, DHCP, DNS, RTP, RTSP, RTMP, NTP, SMB, NFS, TFTP

API ONVIF (Profile S, Profile T), WWS API

Security password protection, strong password policy, HTTPS encryption, WS-Username token, WS-Username basic for ONVIF, TLS1.3

User/host up to 10 users, 2 user levels: administrator and operator

Operating system

Linux SDK

Sensor

Type 1/2.7" progressive scan CMOS

Effective pixels 4M

Lens and illumination

Focal distance 2.8 mm

Aperture F/2.0

Field of view (horizontal) 112°

Field of view (diagonal) 134°

Field of view (vertical) 60°

Angle adjustment (tilt) from 0° to 105°

Angle adjustment (rotate) from 0° to 360°

IR illumination yes

IR range up to 40 m

¹ Under development.

Technical features (continued)

Image	
Image	color
Maximum resolution	2560 × 1440
Maximum frame rate	main stream: 5–30 fps (2560 × 1440, 1920 × 1080, 1280 × 720); sub stream: 5–25 fps (1920 × 1080, 1280 × 720, 960 × 540, 640 × 360)
Bit rate	512 Kbps to 10 Mbps
Video compression	H.264, H.265
Image quality improvement	DNR 2D/3D, DWDR, BLC, AE, AWB, HLC, ANTI-FLICKER, DEFOG
Signal-to-noise ratio	no less than 50 dB
Luminous sensitivity	color: 0.01 lx, bw: 0 lx with IR
Audio	
Built-in microphone	yes
Audio compression	PCM, G.711A (PCMA), G.711U (PCMU), AAC, MP2, MP3
Voice pickup distance	syllabic legibility up to 5 m
Physical specifications	
Power supply	12 V DC, PoE 802.3af (Mode A, Mode B)
RAM	128 MB
ROM	32 MB
Casing	metal, plastic
Form factor	dome camera
Mount options	indoor and outdoor
Dimensions (Height × Diameter)	90 × 110 mm
Weight	0.39 kg
Operating temperature	from -40 to +60 °C
Operating humidity	no more than 90 % (non-condensing)
Ingress protection	IP67

Analytics and protocols

- Motion detection
- Human face recognition
- Human silhouette recognition
- Line crossing¹
- Perimeter intersection¹
- ONVIF (Profile S, T)

Features and capabilities

- Night vision
- Storage: memory card, network storage¹
- Management via web interface
- Non-volatile time (up to 24 hours)

¹ Under development.

Ordering information

Name	Description
SV-BA314-E rev.B	SV-BA314-E rev.B wired IP camera. Mounting kit.

Contact us



+7 (383) 274 10 01
+7 (383) 274 48 48



eltex@eltex-co.ru



eltex-co.com

About Eltex

Eltex Enterprise is a leading Russian developer and manufacturer of communication equipment with 30 years of history. Complete solutions and their seamless integrability into the Customer's infrastructure are the priority growth areas of the company.