

- Bandwidth up to 640 Gbps
- Non-blocking architecture
- 32 ports of 10G
- Front-to-Back cooling
- Stacking up to 8 devices
- Redundant power supplies

MES5312, MES5316A, MES5324A, MES5332A switches are high performance devices with 10GBASE-R/1000BASE-X interfaces that can be used as aggregation switches in carrier networks and data centers.

The devices ports support operation at rates of 1 Gbps (SFP) and 10 Gbps (SFP+), that provides usage flexibility and ability of gradual transition to higher data rates. The non-blocking architecture provides correct packet processing under maximum loads, while maintaining minimal and predictable delays for all types of traffic.

The front-to-back ventilation design ensures effective cooling when using the devices in modern data centers.

Fault tolerance of the devices is ensured by redundant power supplies (1+1) and the use of replaceable fans. The redundant and hot-swappable fans and AC/DC power supplies along with advanced hardware monitoring functions provide high reliability and ensure uninterrupted operation of the carrier networks.

The devices comply with CE requirements.



MES5312



MES5316A



MES5324A



MES5332A

Technical features

	MES5312	MES5316A 	MES5324A 	MES5332A 
Interfaces				
10GBASE-R (SFP+)/1000BASE-X (SFP)	12	16	24	32
10/100/1000BASE-T (OOB)	1			
USB 2.0	—	1	1	1
Console port RS-232 (RJ-45)	1			
Performance				
Bandwidth	240 Gbps	320 Gbps	480 Gbps	640 Gbps
Throughput for 64 bytes ¹	178 MPPS	238 MPPS	238 MPPS	238 MPPS
Buffer memory	2 MB	3 MB	3 MB	3 MB
RAM (DDR3)	1 GB ²			
ROM (NAND Flash)	1 GB			
MAC table	32768			

¹ Values are given for one way transmission.

² RAM for MES5316A rev.C, MES5324A rev.C, MES5332A rev.C, MES5316A rev.C1, MES5324A rev.C1 models is 2 GB.

Technical features (continued)

	MES5312	MES5316A 	MES5324A 	MES5332A 
ARP table ¹			8125	
VLAN table			4094	
L2 Multicast group			4092	
Maximum number of VXLAN	4093	2478	2478	2478
Link Aggregation Groups (LAG)			128, up to 8 ports in one LAG	
Quality of Services (QoS)			8 egress queues per port	
Jumbo frames			10240 bytes	
Stacking			up to 8 devices	

Features and capabilities

Interface features

- Head-of-line blocking (HOL) protection
- Back pressure
- Auto MDI/MDIX
- Jumbo frames
- Flow Control (IEEE 802.3X)
- Port Mirroring (SPAN, RSPAN)
- Stacking

MAC address functions

- Independent learning mode per VLAN
- MAC Multicast Support
- Configurable aging time of MAC addresses
- Static MAC Entries
- MAC Flapping

VLAN functions

- Voice VLAN
- IEEE 802.1Q
- Q-in-Q
- Selective Q-in-Q
- GVRP
- Subnet-based VLAN

L2 Multicast functions

- Multicast groups
- Static Multicast groups
- IGMP Snooping v1,2,3
- Host/port-based IGMP Snooping Fast Leave
- PIM-Snooping
- IGMP proxy-report
- IGMP authorization through RADIUS
- MLD Snooping v1,2
- IGMP Querier
- MVR

L2 functions

- STP (Spanning Tree Protocol, IEEE 802.1d)
- RSTP (Rapid Spanning Tree Protocol, IEEE 802.1w)
- MSTP (Multiple Spanning Tree Protocol, IEEE 802.1s)
- PVSTP+
- RPVSTP+
- Spanning Tree Fast Link option
- STP Root Guard
- BPDU Filtering
- STP BPDU Guard

¹ For each host in the ARP table, an additional entry is created in the switching table. The number of ARP entries with an installed EVPN license for MES5316A, MES5324A, MES5332A is 6135, for MES5312 is 6077.

² The number of MAC/IPv4/IPv6 ACL entries with an installed EVPN license for MES5316A, MES5324A, MES5332A is 2505/2505/1252.

³ IPv4/IPv6 Unicast/Multicast routes share hardware resources. The number of IPv4 Multicast routes with an installed EVPN license is 6085.

Features and capabilities (continued)

- LBD (Loopback Detection)
- ERPS (G.8032v2)
- Flex-link
- Private VLAN
- L2PT (Layer 2 Protocol Tunneling)

Link Aggregation functions

- LAG groups creation
- LACP
- LAG Balancing Algorithm
- MLAG (Multi-Switch Link Aggregation Group)

IPv6 functions

- IPv6 Host
- Dual-stack IPv6, IPv4

Service functions

- Optical transceiver diagnostics
- Green Ethernet

Quality of Service (QoS) and rate limiting

- QoS statistics
- Shaping, Policing
- IEEE 802.1p Class of Service
- Storm control for different traffics (broadcast, multicast, unknown unicast)
- Bandwidth management
- Strict Priority and Weighted Round Robin (WRR) scheduling algorithms
- Three marking colors
- ACL-based CoS/DSCP assignment
- ACL-based VLAN assignment
- Setting the IEEE 802.1p priority for management VLAN
- DSCP to CoS, CoS to DSCP remarking
- 802.1p, DSCP mark assignment for IGMP

OAM

- 802.3ah Ethernet Link OAM
- 802.3ah Unidirectional Link Detection

Management functions

- Configuration file download and upload via TFTP/SFTP/SCP
- SNMP
- CLI (Command Line Interface)
- Web interface
- Syslog
- SNTP (Simple Network Time Protocol)
- NTP (Simple Network Time Protocol), NTP server, NTP peer-to-peer
- Traceroute
- LLDP (802.1ab) + LLDP MED
- LLDP (IEEE 802.1ab)
- Access control – privilege levels for users
- Management ACL
- Management interface blocking
- Local authentication
- IP addresses filtering for SNMP
- Macrocommands
- CLI commands logging
- System log
- DHCP autoprovision
- DHCP Relay (Option 82)
- DHCP Option 12
- DHCP server
- Debugging commands
- Traffic to CPU rate limiting
- Ping (IPv4/IPv6)

¹ BGP protocol support is provided under license.

² EVPN technology support is provided under license.

Features and capabilities (continued)

Monitoring functions

- Interface statistics
- RMON remote monitoring
- IP SLA
- CPU utilization monitoring per task and per traffic type
- Temperature monitoring
- TCAM monitoring

MIB

- RFC 1065, 1066, 1155, 1156, 2578 MIB Structure
- RFC 1212 Concise MIB Definitions
- RFC 1213 MIB II
- RFC 1215 MIB Traps Convention
- RFC 1493, 4188 Bridge MIB
- RFC 1157, 2571-2576 SNMP MIB
- RFC 1901-1908, 3418, 3636, 1442, 2578 SNMPv2 MIB
- RFC 1271, 1757, 2819 RMON MIB
- RFC 2465 IPv6 MIB
- RFC 2466 ICMPv6 MIB
- RFC 2737 Entity MIB
- RFC 4293 IPv6 SNMP Mgmt Interface MIB
- Private MIB
- RFC 2021 RMONv2 MIB
- RFC 1398, 1643, 1650, 2358, 2665, 3635 Ether-like MIB
- RFC 2668 IEEE 802.3 MAU MIB
- RFC 2674, 4363 IEEE 802.1p MIB
- RFC 2233, 2863 IF MIB
- RFC 2618 RADIUS Authentication Client MIB
- RFC 4022 MIB for TCP
- RFC 4113 MIB for UDP
- RFC 3289 MIB for Diffserv
- RFC 2620 RADIUS Accounting Client MIB
- RFC 2925 Ping & Traceroute MIB
- RFC 768 UDP
- RFC 791 IP
- RFC 792 ICMPv4
- RFC 2463, 4443 ICMPv6
- RFC 4884 Extended ICMP for Multi-Part messages support
- RFC 793 TCP
- RFC 2474, 3260 Definition of the DS field in the IPv4 and IPv6 headers
- RFC 1321, 2284, 2865, 3580, 3748 Extensible Authentication Protocol (EAP)
- RFC 2571-2574 SNMP
- RFC 826 ARP
- RFC 854 Telnet
- IEC 61850

Physical parameters

	MES5312	MES5316A	MES5324A	MES5332A
Physical parameters and environmental features				
Power supply	AC: 100–240 V, 50–60 Hz; DC: 36–72 V Power supply options: • 1 AC/DC power supply • 2 hot-swappable AC/DC power supplies			
Input current	0.2–0.3 A for AC 0.3–0.6 A for DC	0.3–0.8 A for AC 0.8–1.8 A for DC	0.3–0.9 A for AC 1.0–2.5 A for DC	0.4–1.0 A for AC 1.1–2.3 A for DC
Maximum power consumption	25 W	58 W	73 W	85 W
Heat dissipation	25 W	58 W	73 W	85 W
Dying Gasp support	no			
Operating temperature	from -10 to +45 °C			
Storage temperature	from -50 to +70 °C			
Operating humidity	no more than 80 % (without condensing)			
Cooling	Front-to-Back, 4 fans			
Maximum acoustic noise level	from the front panel, max < 65.6 dB from the rear panel, max < 71.2 dB			
Form factor	19", 1U			
Dimensions (W × H × D)	430 × 44 × 230 mm	430 × 44 × 275 mm	430 × 44 × 275 mm	430 × 44 × 275 mm
Weight	3.8 kg	3.6 kg	3.7 kg	3.8 kg

Ordering information

Name	Description
MES5312	MES5312 Ethernet switch, 1×10/100/1000BASE-T (OOB), 12×10GBASE-R (SFP+)/1000BASE-X (SFP), L3
MES5316A	MES5316A Ethernet switch, 1×10/100/1000BASE-T (OOB), 16×10GBASE-R (SFP+)/1000BASE-X (SFP), L3
MES5324A	MES5324A Ethernet switch, 1×10/100/1000BASE-T (OOB), 24×10GBASE-R (SFP+)/1000BASE-X (SFP), L3
MES5332A	MES5332A Ethernet switch, 1×10/100/1000BASE-T (OOB), 32×10GBASE-R (SFP+)/1000BASE-X (SFP), L3
Related products	
PM160-220/12	PM160-220/12 power module, 100–240 V AC, 160 W
PM100-48/12	PM100-48/12 power module, 36–72 V DC, 100 W
Related software	
ECCM-MES5312	ECCM-MES5312 option of Eltex ECCM management system for ELTEX network elements management and monitoring: 1 network element MES5312
ECCM-MES5316A	ECCM-MES5316A option of Eltex ECCM management system for ELTEX network elements management and monitoring: 1 network element MES5316A
ECCM-MES5324A	ECCM-MES5324A option of Eltex ECCM management system for ELTEX network elements management and monitoring: 1 network element MES5324A
ECCM-MES5332A	ECCM-MES5332A option of Eltex ECCM management system for ELTEX network elements management and monitoring: 1 network element MES5332A

Contact us

About Eltex



+7 (383) 274 10 01
+7 (383) 274 48 48



eltex@eltex-co.ru



eltex-co.com

Eltex Enterprise is a leading Russian developer and manufacturer of communication equipment with 30 years of history. Complete solutions and their seamless integrability into the Customer's infrastructure are the priority growth areas of the company.